

8 kg pressure seam roller with CENTRAL handle

Code 1018.PR11C

It is an iron roller of about **8 kg** with a **central** handle, which allows the user to stand upright while pressing the seams of the membranes, after having heated them, so as to obtain a perfect bond between them.

8 kg pressure seam roller with LATERAL handle

Code 1018.PR11L

It is an iron roller of about **8 kg** with a **lateral** handle, which allows the user to stand upright while pressing the seams of the membranes, after having heated them, so as to obtain a perfect bond between them. It can be used together with the lap torch (code 1016.JSTK) by just one operator.

SPECIFICATIONS			
Diameter	Width	Weight	
80 mm	150 mm	kg 8	



3 kg pressure seam roller with CENTRAL handle

Code 1018.PR09C

It is an iron roller of about **3 kg** with a **central** handle, which allows the user to stand upright while pressing the seams of the membranes, after having heated them, so as to obtain a perfect bond between them.

SPECIFICATIONS				
Code	Diameter	Width	Weight	
1018.PR09C	45 mm	150 mm	kg 3	



■ Mini seam roller Code 1018.PR20

It is an aluminium roller of about **420** gr to press the overlaps. Thanks to its small size, it can be used to reach the most uncomfortable and difficult corners.



SPECIFICATIONS			
Code	Diameter	Width	Weight
1018.PR20	40 mm	100 mm	gr 420



15 kg maxi pressure seam roller with telescopic handle (adjustable length)

Code 1018.PR15

It is an iron roller of about 15 kg with a central telescopic handle (adjustable length) and a double handgrip, which allows the user to stand upright while pressing the seams of the membranes, after having heated them, so as to obtain a perfect bond between them.

SPECIFICATIONS			
Diameter	Width	Weight	
130 mm	120 mm	kg 15	
	Diameter	Diameter Width	



■ 15 Kg MONO-FORK maxi pressure seam roller with telescopic handle (adjustable length) Code 1018.PR15MF

It is a MONO-FORK iron roller of about 15 kg with a central telescopic handle adjustable in length and a double handgrip, which allows the user to stand upright while pressing the seams of the membranes, after having heated them, so as to obtain a perfect bond.

The mono-fork system ensures a perfect sealing even near vertical walls.

iameter	Width	387 - 1 - 1 - 3
	Widdi	Weight
30 mm	120 mm	kg 15
	30 mm	30 mm 120 mm



■ 11 Kg MONO-FORK maxi pressure seam roller with telescopic handle (adjustable length)

Code 1018.PR19MF

It is a MONO-FORK iron roller of about 11 kg with a central telescopic handle adjustable in length and a double handgrip, which allows the user to stand upright while pressing the seams of the membranes, after having heated them, so as to obtain a perfect bond. The mono-fork system ensures a perfect sealing even near vertical walls.

SPECIFICATIONS			
Code	Diameter	Width	Weight
1018.PR19MF	100 mm	120 mm	kg 11



TELESCOPIC HANDLE


The telescopic handle can be adjusted in length according to the user's height and

■ DOUBLE HANDGRIP

The double handgrip allows the user to take hold of the roller with both hands and to direct it with greater accuracy and effectiveness

■ MONO-FORK SYSTEM

The mono-fork system allows the roller to get closer to vertical walls ensuring a perfect sealing of the edge of the membrane



a central telescopic handle (adjustable length) and a double handgrip, which allows the user to press the membranes, in particular the self-adhesive ones, so as to obtain a perfect bond between them.

SPECIFICATIONS			
Code	Diameter	Width	Weight
1018.PR22	110 mm	250 mm	kg 20



■ 40 kg maxi pressure seam roller with telescopic handle (adjustable length)

It is an iron roller of about 40 kg with a central telescopic handle (adjustable length) and a double handgrip, which allows the user to press the membranes, in particular the self-adhesive ones, so as to obtain a perfect bond between them.

SPECIFICATIONS			
Diameter	Width	Weight	
110 mm	500 mm	kg 40	
	Diameter	Diameter Width	